

**Braid**

Made of **polyester**, as per regulations for anchors.

Code	Ø rope	Length m
01.106.00	8	30
01.106.01	10	30

**Line with chain**

Orange levilene line **as per regulation for anchors**. Fitted with a 2-metre galvanized chain and a shackle for connection to the anchor.

Code	Ø rope	Ø chain	Length m
01.105.00	8	6	30

**Line for chain and rope windlass.**

Made with three-strand white rope and **stainless steel chain link**, the end part can be connected to the windlass chain.

Code	Ø rope	Length m	Gypsy Ø mm	Chain link Ø mm	For windlasses
02.636.01	10	35	6	6	Manual mooring, Lofrans: Project x1; Italwinch 02.407.01
02.636.02	12	35	6	6	Lewmar: Pro-series 1000, V-700, V1, V2 Lofrans: Project x1, Dorado 500W, Marlin; Lewmar CPX0; Italwinch Ray; Italwinch RayLux
02.834.00	14	35	8-10	8	Lewmar: Pro-series 1000, V1, V2, V3, V4 Lofrans: Project x1-x2-x3, Project 1000-1500, Dorado 700W, Clipper 700-1000; Italwinch Thunder, Italwinch ThunderLux
02.636.05	16	40	10	10	Lewmar: Pro-series 1000, V3, V4, V5 Lofrans: Project x2-x3, Project 1000-1500, Clipper 1000; Italwinch Thunder Lux Ø 16


**Anchor rope made of polyester braid with lead core for the first 10 metres**

With thimble and spliced by hand.
It comes in an elegant nylon bag with blue string.

Code	Ø rope	Length m	Lead core length m	Lead weight kg	Total weight kg
06.446.10	10	30	10	3	5
06.446.12	12	30	10	4	7.5
06.446.13	12	50	20	8	10



U Douglas Marine

**Chain Boy chain stowing system****PATENT**

It allows tidy chain stowage on all anchor chain lockers. Minimum locker height when hauling in the anchor: 80 mm for 6/8-mm chain, 100 mm for 10/12-mm chain.

Code	Base Ø mm	Head Ø mm	Adjustable height
01.550.00	150	170	325 to 475 mm by means of the inserts included

**Safety Device Chain Stopper Deluxe in Stainless Steel 316****AISI 316**

The chain stopper device prevents the anchor rode unwanted release while the boat is in use. It also prevents shock/abnormal loading of the windlass while the boat is at anchor. The Chain Stopper can be disengaged with a simple movement.

Code	For chain Ø mm	Base mm	Overhang mm
01.119.34	6/8	60x50	47
01.119.35	10/12	80x70	63

**ITALWINCH steel chain stopper**

Chain lock compatible with main chains from 8 mm to 14 mm diameter with crossbar. Fully made of AISI 316 steel.

Code	Base mm	For chain Ø mm
01.119.50	110x62	8mm ISO - 8 mm DIN 766 - 10mm ISO - 10mm DIN 766
01.119.51	130x85	12mm ISO - 13mm DIN 766 - 13mm DIN 764, 14mm ISO - 12.5 C.T., 14 C.T.

