

Key for valve

Art. 721 / A942010N



BRAVO 2005



BRAVO 2005/A



BRAVO 2005 SUP + MESH




INSTALLATION

- 1. Hole required for valve installation $\varnothing 36 \pm 0.5$ mm
- 2. Tighteninng torque = 30 Nm
The valve assembly should be-retorqued after at least 12 hours
- 3. The users responsibility to ensoure that any fluid used during the installation or operation are compatible with this valve

APPLICABLE STANDARD ISO 15738:2002(E)

VALVES			
ITEM	P/N	COLOR	PRINCIPLE OPENING
BRAVO 2005	A102800N	BLACK	PUSH-PUSH
BRAVO 2005	66.446.44	GREY	PUSH-PUSH
BRAVO 2005	A102802N	DARK GREY	PUSH-PUSH
BRAVO 2005/A	A102815N	BLACK	PUSH-PUSH
BRAVO 2005/A	66.446.64	GREY	PUSH-PUSH
BRAVO 2005/A	A102803N	DARK GREY	PUSH-PUSH
BRAVO 2005 SUP + MESH	66.446.01	GREY	PUSH-PUSH

		BRAVO 2005 INFLATION VALVE		Massa 0.06 kg	
		A1028XXN	Edizione 00	Foglio 1 / 1	