
















## Selectionguide navigation lights

Powercraft less than 7m. max speed 7 knots	Sailing vessels less than 20m (may also be performed)		
			
1 All-round white	1 Tricolor sailing light	*1 All-round red *1 All-round green 1 Port 1 Starboard 1 Stern	*1 All-round red *1 All-round green 1 Bicolor side lantern 1 Stern

Sailing vessels more than 20m	Powercraft less than 20m (may also be performed)	Powercraft less than 50m (may also be performed)
		
*1 All-round red *1 All-round green 1 Port 1 Starboard 1 Stern	1 Masthead 1 Port 1 Starboard 1 Stern	1 Masthead 1 Bicolor 1 Stern
		1 Masthead 1 Port 1 Starboard 1 Stern

Powercraft less than 12m when masthead and stern can't be mounted. Motor driven vessels 12m up to 20m	Motor driven vessels 12m up to 20m		
			
1 All-round white 1 Bicolor	1 All-round white 1 Port 1 Starboard	1 Masthead 1 Bicolor 1 Stern	1 Masthead 1 Port 1 Starboard 1 Stern

Motor driven and sailing boats at anchor, aground or at pier			Vessels restricted in manoeuvrability more than 12m
Less than 50m at anchor	From 12m aground	Less than 50m at pier	
			
1 All-round white	1 All-round white 2 All-round red in vertical line	1 All-round white showing out on boardside	in addition to prescribed navigation light: 1 All-round white 2 All-round red

### TALAMEX LED NAVIGATION LIGHTS

LED navigation light with a strong polycarbonate house equipped with STAINLESS STEEL cover plate.

- For boats up to 12m
- Dimensions W x H x D 64,4mm x 75mm x 55,5mm
- Voltage 12V
- Wattage 0, 54W
- LED rated life 50.000 hours
- IP66
- CE, RoHS



House: black

Art.no	Description
12.543.011	Masthead light 225°
12.543.012	Stern light 135°
12.543.013	Port light 112,5°
12.543.014	Starboard light 112,5°
12.543.015	Combi-light each 112,5°



House: white

Art.no	Description
12.543.031	Masthead light 225°
12.543.032	Stern light 135°
12.543.033	Port light 112,5°
12.543.034	Starboard light 112,5°
12.543.035	Combi-light each 112,5°

### LED SIDELIGHTS SET

LED starboard and port navigation lights with modern design. Supplied including mounting gasket.

- IP67
- 12V
- 0.14A (red) 0.09A (green)
- According IMO COLREG 72 2NM  
USCG, ABYC A-16 and NMMA type accepted
- L x W x H 93mm x 57mm x 36mm



Art.no	Description
12.543.060	ABS black
12.543.061	ABS white
12.543.062	Stainless Steel

### LED COMBILIGHT

Chrome plated bow LED lamp red/green.

- Dimensions L x W x H  
101mm x 79mm x 45mm
- 12V
- IP66



Art.no	Description
12.543.030	LED Combilight

### LED NAVIGATION LIGHTS 360°

360° LED navigation lamp with quickfit bayonet mounting bracket.

- Easy assembly thanks to quickfit
- A rubber gasket in the base provides good water resistance
- IP65
- According to standard USCG 2NM  
COLREG 2 MILE 12V A-16
- Ø 62mm
- Height 60mm



Art.no	Description
12.543.038	White
12.543.039	Black

### LED NAVIGATION LIGHTS 360°

LED 360° navigation lamp with black plastic base.

- IP67
- 12V
- 1,5W
- According to standard IMO COLREG 72, USCG, ABYC A-16 and NMMA type accepted
- Height 10,16cm
- Base size L x W 75mm x 31,5mm



Art.no	Description
12.543.040	Black
12.543.041	White