

MAXSET ANCHORS AND MAXSET BOW ROLLERS

See chart below to select the most suitable bow roller for use with your MAXSET or MAXCLAW anchor.

MAXSET ANCHORS			TO SUIT APPROXIMATE BOAT LENGTH												MAXSET BOW ROLLERS			
Stainless Steel	Galvanised	Weight	4M (13')	6M (20')	8M (26')	10M (33')	12M (39')	14M (46')	16M (52')	18M (59')							Satin Finish	Polished Finish
P105070	P105069	4 kg/9 lbs															P105074	P105075
P105055	P105000	6 kg/13 lbs															P105074	P105075
P105056	P105001	10 kg/22 lbs															P105076	P105077
P105057	P105002	16 kg/35 lbs															P105078	P105079
P105058	P105003	20 kg/44 lbs															P105080	P105081
P105059	P105004	25 kg/55 lbs															P105082	P105083
P105067	P105005	30 kg/66 lbs															P105082	P105083
P105068	P105006	40 kg/88 lbs															P105082	P105083

MAXCLAW ANCHORS			TO SUIT APPROXIMATE BOAT LENGTH													
		Weight	4M (13')	6M (20')	8M (26')	10M (33')	12M (39')	14M (46')	16M (52')	18M (59')						
P105060		5 kg/11 lbs														
P105061		7.5 kg/17 lbs														
P105062		10 kg/22 lbs														
P105063		15 kg/33 lbs														
P105064		20 kg/44 lbs														
P105065		30 kg/66 lbs														
P105066		40 kg/88 lbs														




ANCHOR SWIVEL SHACKLES

Improve your anchor retrieval

The use of a swivel and joining shackle for your anchor and rode will greatly improve anchor retrieval and help ensure that the rode lays neatly into your anchor locker.

Maxwell has two available sizes for use with its automatic rope/chain series windlasses to suit vessels up to 20 metres (65 feet):

- 6-8 mm (1/4" - 5/16")
- 10-13 mm (3/8" - 1/2")



6-8 MM (P104370)



10-13 MM (P104371)

EMERGENCY CRANK/CLUTCH RELEASE HANDLES AND BI-SQUARE EXTENSION DRIVES

Especially for RC and HRC Series

These handles are available in two different sizes to suit the constraints of most foredeck configurations. They are constructed of light weight, durable injection-molded plastic and will float if accidentally dropped overboard.

Bi-square drives are also available in a 150 mm inline extension for use on windlasses mounted in recessed lockers.

A Bi-square to 1/2" square drive adapter which can be used in conjunction with standard 1/2" ratchets and tools.

BI-SQUARE EXTENSION AND 1/2" DRIVE



(7038)



(7369)



10" (P103865)

8" (P103864)

