

## Deck equipment

### Handrail (AISI 316)



**PIJP**



**STEUN..**

### Stainless steel (AISI 316) handrail

Rail pipe and rail fittings available in Ø 20 mm and 25 mm. Pipe is available per metre. Fittings must be ordered separately, please see price list.

Type	Tube Ø	Wall thickness	Max. pipe length
PIJP	20	1,5	6000
PIJP25	25	1,5	6000

Type	Tube Ø	Support
STEUN20V	20	Front
STEUN20A	20	Rear
STEUN20M	20	Middle
STEUN25V	25	Front
STEUN25A	25	Rear
STEUN25M	25	Middle



**STANCH..**


### Stainless steel (AISI 316) stanchions

Tapered with two wire holes. Max. railing wire 9,5 mm.



Type	Length	Height	C - C	D1	D2	D3	Hole spacing
STANCH61	619	610	305	10,1	10,1	8	2 wire holes at 305 / 610
STANCH75	759	750	360	10,1	10,1	8	2 wire holes at 360 / 750



**STANCHPR**



**STANCHPS**



### Stainless steel (AISI 316) stanchion sockets

#### Specifications

- Diameter: 25 mm
- 90° straight or with 6° angle

Type	Description
STANCHPR	Straight
STANCHPS	Angled

