

Electric toilet unit

OSCULATI

Fitted with **bronze** self-priming pump and neoprene rotor. Push-button operated, permanent-magnet motor and **stainless steel** shaft, built-in macerator. White seat and cover. 19-mm (3/4") inlet pipe and 25-mm (1") outlet pipe. Control panel INCLUDED.

Spray Nozzle washing fitting for faster and more effective cleaning at very high pressure on all the toilet bowl surface.

Code	Bowl	Board	Model	V	A	mm			kg
						Height	Width	depth	
50.207.13	white porcelain	soft close plastic	Space Saver	12	15	340	345	420	14
50.205.13	white porcelain	White lacquered wood	Space Saver	12	15	340	345	420	14
50.207.12	white porcelain	soft close plastic	compact	12	15	370	345	420	14.5
50.207.24	white porcelain	soft close plastic	compact	24	7.5	370	345	420	14.5
50.205.12	white porcelain	White lacquered wood	compact	12	15	370	345	420	14.5
50.205.24	white porcelain	White lacquered wood	compact	24	7.5	370	345	420	14.5
50.206.12	white porcelain	big soft close plastic	Large	12	15	385	365	490	14.5
50.206.24	white porcelain	big soft close plastic	Large	24	7.5	385	365	490	14.5



50.207.23 Gasket kit for electric toilet unit.

50.204.44 Electric control panel



▲ 50.207.13



▲ 50.205.12/24



▲ 50.205.13



▲ 50.206.12/24



▲ 50.207.12/24



▲ 50.204.44

OSCULATI

Evolution electric toilet unit

LOW NOISE

Fitted with special self-priming pump reducing by 80% the typical noise of electric toilets.

Permanent magnet motor, built-in macerator.

19-mm (3/4") inlet hose, 25/38-mm (1"-1 1/2") outlet hose. Control panel included. White ceramic bowl, technopolymer Soft Close seat. 360° adjustable drain fitting. 360° swivel drain fitting.

Code	Model	V	A	mm		
				Height	Width	depth
50.245.12	Space Saver	12	19	335	330	420
50.246.12	compact	12	17	385	330	420
50.246.24	compact	24	8	385	330	420



50.207.14 Impeller, seals and valves kit



▲ 50.245.12



▲ 50.246.12/24

JABSCO

JABSCO electric toilet

White vitreous china bowl, wooden seat. Push button switch included. 19-mm inlet hose, 25-mm outlet hose. Self-priming pump up to 1.2 m. It can be installed up to 90 cm below the waterline.

Code	V	Fuse	mm	kg
50.225.12	12	25A	350x430x350 (H)	15.4
50.225.24	24	15A	350x430x350 (H)	15.4



50.225.00 Service kit with impeller, seals and O rings.

50.207.28 Wooden board

