

**ROPE AND CHAIN**

Maxwell can supply a full range of anchor rodes including chain-only, rope only or a pre-spliced combination of rope and chain rodes. Chains for vessels up to 100 metres (300 feet) and 8-plait (brait) nylon rope for vessels up to 20 metres (65 feet) in length as well as ropes and hawsers commonly used on superyachts.

Please see the pictures shown on this page for sizes and characteristics.

STANDARD COMBINATION ROPE CHAIN KITS						
CHAIN Ø	CHAIN LENGTH	ROPE Ø	ROPE LENGTH			
			50 m	100 m	150 m	200 m
6 mm	10 mtrs	12 mm	SP2627	SP2628	SP2629	SP2630
6 mm	20 mtrs	12 mm	N/A	SP2643	N/A	N/A
8 mm	10 mtrs	14 mm	SP2631	SP2632	SP2633	SP2634
8 mm	20 mtrs	14 mm	SP2644	SP2642	N/A	N/A
10 mm	10 mtrs	16 mm	SP2648	SP2649	N/A	N/A
10 mm	20 mtrs	16 mm	SP2645	SP2646	N/A	N/A

Custom lengths available. Contact your Maxwell Dealer.



**NYLON 8 PLAIT ROPE**

**12MM (SP3167) 14MM (SP3168)**  
**16MM (SP3169) 20MM (SP3170)**

**CHAIN SNUBBERS**

*Alternative method of taking the load of your windlass*

These snubbers are recommended to secure the anchor while under way. Available in rope version with chain clevis hook.



Type	Description
SP3174	6 mm chain hook 1.5 mtrs Ø12 mm Nylon 8 Plait rope
SP3175	8 mm chain hook 1.5 mtrs Ø14 mm Nylon 8 Plait rope
SP3176	10 mm chain hook 2 mtrs Ø16 mm Nylon 8 Plait rope

**ANCHOR TENSIONER**

*Simple, easy to use and adjustable tensioner*

This innovative anchor tensioner secures the anchor firmly into the bow roller, taking the weight off the windlass and preventing accidental deployment of the anchor. The tensioner is suitable for use with 7 mm (¼") to 12 mm (½") short link chain and can be secured to an existing cleat or bollard so no installation is required.

