

Pipes



Reinforced PVC hose

In **flexible PVC**, non-toxic for food with polyester thread reinforcement; ideal for water distribution and bilge pumps.

Food-grade hose compliant with CE standards.

Operating temperature -10°C to +60°C.

Code	Ø mm	Pressure bar	Roll m	Code	Ø mm	Pressure bar	Roll m
18.001.10	10x16	15	100	18.001.19	19x26	10	50
18.001.12	12x18	15	100	18.001.25	25x33	6	50
18.001.15	15x21	10	50	18.001.30	30x38	6	50



Spiral reinforced hose for WCs, pumps, etc.

In **transparent PVC with a spiral in white PVC**, very soft, accepts tight curves without collapsing. **Food-grade hose compliant with CE standards.** Operating temperature -10°C to +60°C.

Code	Inside Ø mm	External Ø mm	Thickness mm	Minimum bend radius mm	Pressure bar	Roll m
18.006.14	14	20	2.5	40	6	30
18.006.16	16	22	3	50	6	30
18.006.20	20	26	3	60	5	30
18.006.25	25	32	3.5	75	5	30
18.006.30	30	37	3.5	90	4.5	30
18.006.38	38	46	4	115	4	30



Traditional spiral hose for plumbing, pumps, etc.

In **transparent PVC with a steel spiral**. Very soft, accepts curves up to one time the outer diameter without flattening.

Ideal for inlet and outlet at sea. Food-grade hose compliant with CE standards. Operating temperature -10°C to +60°C.

Code	Ø mm	Pressure bar	Roll m	Code	Ø mm	Pressure bar	Roll m
18.002.12	12x18	7	60	18.002.38	38x49	4	30
18.002.14	14x20	6	60	18.002.40	40x53	3	30
18.002.15	16x22	6	60	18.002.45	45x55	3	30
18.002.16	18x25	6	60	18.002.50	50x65	3	30
18.002.20	20x27	5	60	18.002.60	60x75	2.5	30
18.002.25	25x34	5	60	18.002.70	70x86	2	30
18.002.30	30x40	4.5	60	18.002.80	80x97	2	30
18.002.35	35x46	4	30				



Special PREMIUM hose WC pipes, pumps and wash basins

In **white PVC anti-sweat odour**, with internal **steel spiral**, very flexible and robust. Operating temperature -15°C to +60°C.

Code	Ø mm	Curve radius mm	Pressure bar	Roll m
18.003.20	20x27	50	5	60
18.003.25	25x33	75	5	60
18.003.40	38x48	115	4	30
18.003.41	40x50	120	4	30



SUPERFLEX spiral hose

In **grey PVC with steel spiral**. It has a particularly soft compound that allows it a **flexibility comparable to a rubber hose**. The surface is treated to make it similar to a silicone hose, giving it a very technical and professional appearance. Operating temperature -10°C to +60°C.


Code	Ø mm	Pressure bar	Roll m	Code	Ø mm	Pressure bar	Roll m
18.007.16	16	5	60	18.007.30	30	4	30
18.007.20	20	5	60	18.007.38	38	4	30
18.007.25	25	4	60				



Sanipomp-extra odour-resistant rubber tube for WC

Smooth, extremely robust spiral rubber hose used as a connection for boat toilet discharge. Prevents the spread of odours from toilet discharge. The materials used ensure a smooth, non-stick, odourless internal surface, resistant to bacterial flora formation, acids, bases, with a low friction coefficient and low permeability. Also used for connecting biological tanks, biological pumps, and bilge pumps in leisure boats. Operating temperature -40°C to +120°C.

Code	Ø mm	Exterior color	Radius of curvature	Pressure bar	Roll m
18.011.19	19	☐ white	40	7	40
18.011.25	25	☐ white	50	7	40
18.011.30	30	☐ white	60	7	40
18.011.38	38	☐ white	80	7	40
18.011.51	51	☐ white	100	7	40



Anti-odour Sanitation hose

Compared to plastic tubes, it offers the advantage of greater flexibility. The inner surface is smooth, non-stick, odourless, resistant to bacterial flora, acids, etc. Operating temperature -30°C to +80°C.

Code	Ø mm	Curve radius mm	Pressure bar	Roll m
18.005.16	16x24	50	7	30.5
18.005.19	19x27	60	7	30.5
18.005.25	25x33	75	7	30.5
18.005.38	38x47	115	7	30.5