Non-reversible rotary steering system T 73 RFC

Designed for hulls up to 9/10 meters and speed up to 50 MPH. This system allows you to leave the steering wheel without having the propeller cause vibration to the hull.

| "T 73" control box | M66 cable | Cover | | |
|--------------------|------------|-----------------|-------------------|-----------------|
| only | only | 90° color black | 90° chromed color | 20° black color |
| 45.073.00 | 45.185.xx* | 45.055.05 | 45.05.05 | 45.055.03 |




45.595.13; 45.595.14; 45.595.15; 45.595.16; 45.595.17; 45.595.18; 45.595.19 side terminals and brackets for any kind of steering wheel from this catalogue (OPTION).

Enaine



Pls refer to the detailed table at the end of the rotating system range to choose a cable of the right length.



✓ Planetary



Rotary steering system with adjustable wheel orientation

| 45.081.00 T81 FC Single for boats up to 9/10 metrers 45.185.xx* 45.038.00 | Control box | Model | Version | M66 cable only | Hub at 90° with mechanism for tilt up to 48° |
|---|----------------|--------|---|----------------|--|
| | 45.081.00 | T81 FC | Single for boats up to 9/10 metrers | 45.185.xx* | 45.038.00 |
| 45.083.00 T83 Single non reversible for boats up to 9/10 m 45.185.xx* 45.038.00 | 45.083.00 | T83 | Single non reversible for boats up to 9/10 m | 45.185.xx* | 45.038.00 |



45.595.13; 45.595.14; 45.595.15; 45.595.16; 45.595.17; 45.595.18; 45.595.19 Terminals and brackets for any kind of steering wheel from this catalogue (OPTION).



Pls refer to the detailed table at the end of the rotating system range to choose a cable of the right length.



Planetary gear design







T91/T93ZT rotary steering systems

Features: high efficiency; patented M90 Mach quick-coupling cable. Attention: M90 Mach cable is also suitable for use with steering wheels using M66 cables but these latter are not fit for T91/T93ZT steering systems; Engine side stainless steel cable with watertight seal; Central shaft for easy installation; 4.2 steering wheel turns, 228-mm cable stroke, 408-mm \varnothing steering wheel, 200-mm minimum steering cable bend radius. Recommended for boats not faster than 50 MPH. Not to be used on boats equipped with engines that exceed the maximum HP rating of the boat. T93ZT non-reversible version. It isn't necessary to remove the steering wheel since the propeller rotation will not make the boat veer.

| Code | Description | M90 Mach cable | 90° color black | Cover 90° chromed color | 20° black color | Anti-theft device with chromed hub cover |
|-----------|--------------------------------|----------------------|--------------------|-------------------------------|--------------------|--|
| 45.060.00 | Single steering system | 45.186.xx | 45.055.02 | 45.055.05 | 45.055.03 | 45.055.06 |
| 45.061.00 | Non reversible steering system | 45.186.xx | 45.055.02 | 45.055.05 | 45.055.03 | 45.055.06 |









gear design











T101/T103ZT rotary steering systems with adjustable wheel orientation

MPH speed. Do not install on boats with more powerful engines.

| Code | Description | M90 Mach cable | 90° hub for inclination of steering system up to 48° |
|-----------|--------------------------------|----------------|--|
| 45.062.00 | Single steering system | 45.186.xx | 45.038.00 |
| 45.063.00 | Non reversible steering system | 45.186.xx | 45.038.00 |
| | | | |



