

Valve for waste water systems

Can be used in two ways:

- 1) the toilet drains into the sea or onto the waste water tank with a safety block on the lever, made in accordance with **ISO 8099 standards**
- 2) from the waste water tank the macerator is loaded onto the sea or dock with a back pump.

Classic valve

Made of **ABS**, ready for remote control with a push-pull cable.



Code	Tube Ø mm	←→ mm
50.233.38	38	140x150x150

STRONG valve

Made of **nylon reinforced** with fibers, meets with ISO 8099 standards. Fitted with outlets size **38/25 mm** + bulkhead extension cord that enables for non-visible handle mounting and keeps the valve hidden, the handle can be locked with a padlock.



Code	Tube Ø mm	←→ mm
50.234.00	38/25	200x80x60

Whale valve

Wall mounting or mounting behind the bulkhead.


Code	Tube Ø mm	←→ mm
17.713.00	38	104x180
17.713.01	25	-



Gate valve fitted with lock for waste water tanks

Made of chromed brass, **stainless steel handle** with perforated hole for fitting a padlock; ideal for meeting with ISO 8099 standards concerning waste water draining regulations.

Code	Size
17.228.55	1" 1/4
17.228.56	1" 1/2




3-way sphere valves

AISI 316

Made of **AISI 316 stainless steel**; fitted with handle lock, meets with ISO 8099 standard for waste water drainage regulations.

Code	Size
17.722.05	1" 1/4
17.722.06	1" 1/2



3-way ELECTRIC Y-valve

Electrified valve based on the manual version 50.234.00. With ON-OFF-ON switch to start the valve from either the control panel or the cabin. Designed to be used manually in case of failure. For pipes Ø 38/25 mm. External dimensions mm 250x180x200. Absorption 1.5 ampere 12 V.

Volt	COMPLETE electric valve	Kit to electrify valve 50.234.00	Optional panel with fuse and switch
12	50.230.12	50.231.12	-
24	50.230.24	50.231.24	50.232.00



Reduction joints INCLUDED



Electro-valve

To be used in toilets that use the fresh water from the onboard system. It also works as an anti-siphon to prevent possible backflow of toilet water into the onboard system.

Code	Version	V	Hose adaptor
50.203.10	Brass	12	1/2"
50.203.11	Brass	24	1/2"
50.203.20	Technopolymer	12	14 / 19 / 1/2"
50.203.21	Technopolymer	24	14 / 19 / 1/2"



Black water tank spare valve

Code 50.141.98
OSCULATI black water tank spare valve. 1" 1/2 female thread.

