

VICTRON battery chargers and devices



VICTRON Bluesmart IP65 battery charger with Bluetooth connection

IP65

These battery chargers with built-in Bluetooth enable you to set and configure the information of your charger from your smartphone, tablet or computer, using the VictronConnect app.

180-265 V AC power supply, charge level LED indicator.

Seven step smart charge algorithm, ideal for sealed batteries. Suitable for any kind of batteries, Li-ion batteries included. Automatic compensation for high or low temperature. Low power mode to charge smaller batteries. Recovery of fully discharged 'dead' batteries. Automatic power supply function.

LOW system for charging small batteries. Program to recover a fully discharged battery. Automatic feeding function.

Supplied accessories: connection pliers, M8 eyelets.

Code	Type	Output voltage	Max charging current A	Number of outputs	↔ mm	kg
14.273.06	12/4	14.4	4	1	47x95x190	0.9
14.273.08	12/7	14.4	7	1	47x95x190	0.9
14.273.11	12/10	14.4	10	1	60x105x190	0.9
14.273.16	12/15	14.4	15	1	60x105x190	0.9
14.273.14	12/25	14.4	25	1	75x140x240	0.9
14.273.19	24/13	28.8	13	1	75x140x240	0.9



14.273.20 6-mm cable with eyelets (motor battery)

14.273.21 OPTIONAL standard cigarette lighter plug cable

14.273.22 Cable with pliers



VICTRON Bluesmart IP67 battery charger with Bluetooth connection

IP67

The Victron-connect App connects your smartphone, tablet or computer via Bluetooth to your battery charger for initial configuration and data upload.

Power supply 180-265 VAC. Charging algorithm in 4 stages. BULK - ABSORPTION - FLOAT - STORAGE.

Less ageing and maintenance of the battery when not in use, with the STORAGE MODE system. Protection against overloads, short circuit, overheating. Efficiency 92% and above, with very low heat dispersion.

Code	Type	Output voltage	Max charging current A	Number of outputs	↔ mm	kg
14.273.13	12/13	14.4	13	1	85x211x60	1.8
14.273.18	12/17	14.4	17	1	99x219x65	2.4
14.273.26	12/25	14.4	25	1	99x219x65	2.4
14.273.28	24/12	28.8	12	1	99x219x65	2.4



VICTRON Bluesmart IP22 Bluetooth-enabled battery charger

IP22

Use the App Victron-connect to connect this battery charger to your smartphone, tablet or computer via Bluetooth in order to perform the first configuration and see all the charge data.

Power supply: 180/265 VAC 45/65 Hz 250/350VDC.

6-stage charge: TEST - BULK - ABSORPTION - RECONDITION - FLOAT - STORAGE, with LED for charge level control.

Microprocessor control system to adapt the charge type to the battery requirements.

Protection against: short circuit, reverse polarity, overtemperature.

Storage mode to automatically reduce float voltage to 13.2V to minimize gassing and corrosion of the positive plates.

IP22. Suitable for any battery type, Li-ion included.

Code	Type	Output voltage	Max charging current A	Number of outputs	↔ mm	kg
14.272.10	12/15	14.4	15	1	235x108x65	1.4
14.272.12	12/20	14.4	20	3	235x108x65	1.4
14.272.14	12/20	14.4	20	1	235x108x65	1.4
14.272.15	12/30	14.4	30	3	235x108x65	1.4
14.272.16	12/30	14.4	30	1	235x108x65	1.4
14.272.18	24/16	28.8	16	3	235x108x65	1.4
14.272.17	24/16	28.8	16	1	235x108x65	1.4