


Polybridge II folding gangplank made of carbon

FPT (technical polyurethane) construction. Anodized aluminium hinges. Anti-slip floor safe also in case of wet surface.


Wheels with stainless steel case to lift the gangplank. Double pivoting lock.

It can be mounted with a single pin to let the gangplank swing, or with two pins for mere tilting.

Code	Length m	Width cm	Length when folded m	Thickness when folded cm	Safety capacity kg	 kg	OPTIONAL fastening bushing
42.663.00	2.2	34	1.1	14	140	8	42.659.10; 42.659.25; 42.660.25

**CARBONBRIDGE folding carbon gangway**

High-Tech monocoque body made of carbon fibres previously impregnated with epoxy resins. High-resistance aluminium hinges, machined from solid and thick anodized in black colour. Aluminium pivoting pin. Antiskid walking surface.

Code	Length m	Width cm	Safety capacity kg	 kg	OPTIONAL fastening bushing
42.665.00	2.2	35	150	6.5	42.659.10; 42.659.25; 42.660.25; 42.644.00

**Replacement bushing for gangways**

Made of nylon.

Code	Flange Ø mm	Hole Ø mm
42.659.10	80	25

Bushing for gangway swivel AISI 316

Made of AISI 316 stainless steel, fitted with lower water drain and cap.

Code	Flange Ø mm	Hole Ø mm
42.659.25	80	25

Adjustable bushing (+-30°)

AISI 316

Suitable for providing wall supports to the gangways; made of mirror polished AISI 316 stainless steel.

Code	Mounting base mm	Suitable for gangway shaft	counter plate
42.660.25	100x80	25 mm	INCLUDED

**Side bushing for gangway stanchions**

Made of chromed brass.

Code	Ø hole mm	mm
42.644.00	25	60x68x33

**Balance gear**

Made of polished stainless steel, suited for supporting gangways; supplied with 3 shackles on the 3 corners for fitting into the stern stay or into the halyard and into 2 gangway support wires.

Code	width cm
42.770.00	50

