



OSCULATI**Anchor connector without protrusions****AISI 316**

Anchor connector made of **AISI 316 stainless steel without protrusions**. It lets the anchor chain slide smoothly through the bow roller and avoids entangling of the shackle.


Code	Chain Ø mm	B mm	C mm	L mm	G mm	P mm	H mm
01.220.01	6/8	10	7	16	22	9	90
01.220.02	9/10	13	11	19	29	11	115

OSCULATI**Anchor swivelling connector****AISI 316**

Made of **precision-cast AISI 316 stainless steel** without protrusions, used to connect the chain to the anchor. It lets the anchor chain slide smoothly through the bow roller and avoids entangling of the shackle. **New reinforced model with additional finish, exclusively made by Osculati.**


Code	Chain Ø mm	Breaking load kg	B mm	C mm	L mm	G mm	P mm	H mm
01.740.08	6/8	3500	10	7	16	21	9	95
01.740.09*	6/8	-	10	7	17	20	10	90
01.740.10	9/10	6150	13	11	21	28	11	120

*Suitable for 20-kg Trefoil® anchors

OSCULATI**Anchor maxi swivelling connector****AISI 316**


Made of **mirror polished AISI 316 stainless steel**. Used to connect the chain to the anchor, **maxi** version for 12/14 mm chains.

Code	Chain Ø mm	Breaking load kg	B mm	C mm	L mm	G mm	P mm	H mm
01.740.12	12/14	9470	19	14	29	30	23	140

U Douglas Marine**Mega swivelling anchor connector made from CNC-machined bar****AISI 316**

Made of **polished AISI316 stainless steel**.

Code	For anchors kg	Chain Ø mm	Breaking load kg	B mm	C mm	L mm	G mm	P mm	H mm
01.740.16	50/80	14/16	15000	35	20	20	36	18	176
01.740.17	up to 100	up to 18	26000	38	24	20	36	18	176

OSCULATI**Anchor double-joint swiveling connector****AISI 316**

Made of **AISI 316 stainless steel without protrusions**. This double-joint swivelling connection is the evolution of the single-joint 01.740.08/10 model.

Code	Chain Ø mm	Total length mm	B mm	C mm	L mm	G mm	P mm	H mm
01.742.08	6/8	117	9	8	16	21	10	95
01.742.10	9/10	155	13	10	19	28	13	120

OSCULATI**Twist joint still turns****PATENT****AISI 316**

Made of **mirror-polished AISI316 stainless steel**. With the latest asymmetric anchors (Bruce, Delta, Trefoil® etc.), when the anchor is raised, it most probably turns the wrong side. **The Twist swivelling connector turns the anchor correctly and it reeves into the roller or hawsehole.** A shackle connects the fixed eye to the anchor.

Code	Chain Ø mm	Connecting shackle	A mm	B mm	C mm
01.738.01	6/8	01.080.10	220	60	28
01.738.02	10/12	01.080.10/12/14	320	83	38

