




Bow roller with fairlead

In **stainless steel 304 satin** for mounting above or below the dolphin striker

Code	Length mm	Width mm	Spare sheave	kg
01.118.86	393	52	01.218.82	1.1
01.119.94	500	84	01.219.94	2.6
01.119.95	588	98	01.219.95	3.5



Bow rollers for small vessels

AISI 316


Mirror-polished stainless steel with thermopolymer sheave.

Code	Length mm	Width mm	Height mm	Spare sheave
01.118.80	205	45	53	01.346.51

OSCULATI



01.484.12/14



Bow roller for anchor retrieval

In **stainless steel 304, Chromelux®** finish, complete with **nylon** pulley and upper safety pin.

Code	Length mm	Width mm	Height mm	Version	Spare sheave	kg
01.484.12	210	57	70	Standard	01.346.50	0.63
01.484.13	210	57	70	With anchor locker	01.346.50	1
01.484.14	170	57	70	short	01.346.50	0.55

OSCULATI



Cast AISI316 stainless steel bow roller, compact version

AISI 316

Mirror-polished **precision-cast AISI 316 stainless steel** bow roller with **nylon** sheave.

Code	Length mm	Width mm	Height mm	Base mm	Spare sheave	kg
01.484.09	155	62	75	90x62	01.346.50	0.68

OSCULATI



AISI316 cast bow roller


AISI 316

Mirror-polished **precision-cast AISI316 stainless steel**, white **nylon** sheave. Universal for lines or chains up to approximately 10 kg.

Code	Length mm	Width mm	Height mm	Base mm	Spare sheave	kg
01.484.10	221	82	80	132x82	01.346.30	2

Roller

Constructed from **polished 304 stainless steel**. Pulleys in **nylon**.



Code	A mm	B mm	C mm	Plate thickness mm	Suitable for anchors max kg	kg
01.332.01	200	54	80	2	7.5	0.59
01.332.02	270	54	80	2	10	0.71