

PRODUCT FEATURES

- Windlass monitoring from the helm
- Simple Plug & Play sensor installation
- Accurate information for all-chain or combination rope/chain rodes
- Flexibility of magnet and sensor gap from 3 mm to 50 mm
- Easy set up
- Multiple unit installation options - combine with other Maxwell AA products for total windlass control
- Fits all DC, AC and hydraulic windlasses
- Inbuilt diagnostics for troubleshooting installation issues
- EMC protection to CE EN60945

MAXWELL AA710 WIRELESS, HAND HELD REMOTE WINDLASS CONTROLLER AND RODE COUNTER

All the features of the AA560 plus options to control a bow thruster or deck lights and anchor wash.

- High level wireless transmission security - 2.4GHz ISM band
- Hand held controller displays rode count plus signal strength and battery level
- Water resistant to IP67
- Console requires two AA batteries
- Rubber molding for grip and non-slip protection
- Ergonomic shape with wrist strap connector
- Console holder and protective cover
- Shockproof
- EEE 802.15.4 compliant

Kit includes: one hand held remote control and one base station, one sensor and one magnet.

Note: Two base stations can be operated by one remote to allow control of two windlasses. Plug and Play connectors, T-Connectors and Gender Adapters are also available. Contact your Maxwell Dealer.



(P102981)

MAXWELL AA560 WIRED PANEL MOUNT WINDLASS CONTROLLER AND RODE COUNTER

(P102944)



SPECIAL FEATURES

- Preset stopping point and docking alarm on retrieval
 - One-touch function to deploy and retrieve a preset length of rode
 - Adjustable back lit display in feet, metres or fathoms
 - Graphic LCD screen featuring intuitive user interface for simple operation
 - Displays windlass speed and direction
 - Safety lock to help protect against accidental windlass deployment
 - Logs windlass operation hours to help ensure regular windlass maintenance
 - Weather cover and choice of black or gray console
- Kit includes one console, one sensor and one magnet

MAXWELL AA150 WIRED PANEL MOUNT RODE COUNTER

- Docking alarm
 - Standard 60mm (2.36") marine instrument console
 - Choice of feet or metre count readout
 - Large, adjustable, backlit LCD display
- Kit includes one console, one sensor and one magnet



(P102939)

AUTOANCHOR WIRED ROVING REMOTE CONTROL UNITS

ANCHOR LAUNCHING OR RETRIEVAL FROM THE BOW WHEN VISION FROM THE HELM STATION IS OBSTRUCTED

- Use for Windlasses, Davits, Thrusters and other Marine Equipment
- Electrical protection against back-emf
- Rubber over-molding for shock protection and grip
- Stowage cradle
- Operate in parallel with all AutoAnchor™ products, toggle switches, foot switches or other control equipment
- Connect to DC, AC and Hydraulic systems
- Rugged 4.5 m coiled cable and connectors
- All products are rated to IP67 including cables, plugs and sockets
- Deck socket with 2 m flying lead reduces potential for corrosion (excluding AA320 series)
- Other Maxwell AutoAnchor controllers are available, check with your local Maxwell distributor



**Gender Adapter
Cable Connector
(SP4192)**



**Dual Installation
T Connector
(SP4155)**



4 metres cable

**AA730
With Rode Counter
(P102994)**



**AA320
Windlass Control
(P102992)**

**AA342*
Dual Windlass Controller
(P102996)**

All wires remotes are complete with moulded deck socket Rated to IP67.

* AA341 Model (P102995) is similar to AA342 but can be used as a general dual equipment controller (contact Maxwell for details).

