
















## Selectionguide navigation lights

| Powercraft less than 7m. max speed 7 knots  | Sailing vessels less than 20m<br>(may also be performed)                          |  |   |
|---|---|--|---|
|  |  |  |  |
| 1 All-round white   | 1 Tricolor sailing light  | *1 All-round red<br>*1 All-round green<br>1 Port<br>1 Starboard<br>1 Stern         | *1 All-round red<br>*1 All-round green<br>1 Bicolor side lantern<br>1 Stern         |

| Sailing vessels more than 20m  | Powercraft less than 20m<br>(may also be performed)                                | Powercraft less than 50m<br>(may also be performed)                                 |
|--|--|---|
|  |  |  |
| *1 All-round red<br>*1 All-round green<br>1 Port<br>1 Starboard<br>1 Stern         | 1 Masthead<br>1 Port<br>1 Starboard<br>1 Stern                                     | 1 Masthead<br>1 Bicolor<br>1 Stern  |
|  |  | 1 Masthead<br>1 Port<br>1 Starboard<br>1 Stern                                      |

| Powercraft less than 12m when masthead and stern can't be mounted. Motor driven vessels 12m up to 20m | Motor driven vessels 12m up to 20m  |  |   |
|---|---|--|---|
|                    |  |  |  |
| 1 All-round white<br>1 Bicolor  | 1 All-round white<br>1 Port<br>1 Starboard  | 1 Masthead<br>1 Bicolor<br>1 Stern   | 1 Masthead<br>1 Port<br>1 Starboard<br>1 Stern  |

| Motor driven and sailing boats at anchor, aground or at pier                        |   |  | Vessels restricted in manoeuvrability more than 12m                                   |
|---|---|--|---|
| Less than 50m at anchor   | From 12m aground  | Less than 50m at pier  |   |
|  |  |  |  |
| 1 All-round white   | 1 All-round white<br>2 All-round red in vertical line                               | 1 All-round white showing out on boardside   | in addition to prescribed navigation light:<br>1 All-round white<br>2 All-round red   |

### TALAMEX LED NAVIGATION LIGHTS

LED navigation light with a strong polycarbonate house equipped with STAINLESS STEEL cover plate.

- For boats up to 12m
- Dimensions W x H x D 64,4mm x 75mm x 55,5mm
- Voltage 12V
- Wattage 0, 54W
- LED rated life 50.000 hours
- IP66
- CE, RoHS



House: black

| Art.no     | Description             |
|------------|-------------------------|
| 12.543.011 | Masthead light 225°     |
| 12.543.012 | Stern light 135°        |
| 12.543.013 | Port light 112,5°       |
| 12.543.014 | Starboard light 112,5°  |
| 12.543.015 | Combi-light each 112,5° |



House: white

| Art.no     | Description             |
|------------|-------------------------|
| 12.543.031 | Masthead light 225°     |
| 12.543.032 | Stern light 135°        |
| 12.543.033 | Port light 112,5°       |
| 12.543.034 | Starboard light 112,5°  |
| 12.543.035 | Combi-light each 112,5° |

### LED SIDELIGHTS SET

LED starboard and port navigation lights with modern design. Supplied including mounting gasket.

- IP67
- 12V
- 0.14A (red) 0.09A (green)
- According IMO COLREG 72 2NM  
USCG, ABYC A-16 and NMMA type accepted
- L x W x H 93mm x 57mm x 36mm



| Art.no     | Description     |
|------------|-----------------|
| 12.543.060 | ABS black       |
| 12.543.061 | ABS white       |
| 12.543.062 | Stainless Steel |

### LED COMBILIGHT

Chrome plated bow LED lamp red/green.

- Dimensions L x W x H  
101mm x 79mm x 45mm
- 12V
- IP66



| Art.no     | Description    |
|------------|----------------|
| 12.543.030 | LED Combilight |

### LED NAVIGATION LIGHTS 360°

360° LED navigation lamp with quickfit bayonet mounting bracket.

- Easy assembly thanks to quickfit
- A rubber gasket in the base provides good water resistance
- IP65
- According to standard USCG 2NM  
COLREG 2 MILE 12V A-16
- Ø 62mm
- Height 60mm



| Art.no     | Description |
|------------|-------------|
| 12.543.038 | White       |
| 12.543.039 | Black       |

### LED NAVIGATION LIGHTS 360°

LED 360° navigation lamp with black plastic base.

- IP67
- 12V
- 1,5W
- According to standard IMO COLREG 72, USCG, ABYC A-16 and NMMA type accepted
- Height 10,16cm
- Base size L x W 75mm x 31,5mm



| Art.no     | Description |
|------------|-------------|
| 12.543.040 | Black       |
| 12.543.041 | White       |