

Heavy Duty fender

White body and blue head. Fitted with inflation/deflation valve. Models OF4/OF6 can also be used as hull hauling rollers. 0.15bar max pressure.

Code	Model	⊙		⊠		♻️ PACKAGE
		cm	in	cm	in	
33.212.09	OF1	15	6	61	24	10
33.212.10	OF2	21	8	61	24	10
33.212.11	OF3	21	8	74.5	29	10
33.212.12	OF4	20.2	8	104	41	5
33.212.18	OF5	26.8	11.5	78	30.5	5
33.212.13	OF6	26.8	11.5	109	43	5



OSCULATI



Heavy Duty fender and buoy

White body and blue head. Fitted with inflation/deflation valve. 0.15bar max pressure.

Code	Model	⊙		⊠		♻️ PACKAGE
		cm	in	cm	in	
33.300.12	OA1	30	11.5	38	15	10
33.300.27	OA2	39	15.4	50	19.5	10
33.300.50	OA3	46	18.1	58	22.9	10



OSCULATI



New TFG series fender

Fitted with inflation valve.

Model	Colour white	⊙		⊠		kg	♻️ PACKAGE
		cm	in	cm	in		
TFG 0	33.539.01	9	3 1/2	33	13	0.35	20
TFG 1	33.539.02	11	4 1/2	40	16	0.50	10
TFG 2	33.539.03	14	5 1/2	50	20	0.85	6
TFG 3	33.539.04	16	6 1/2	58	23	1.1	4
TFG 4	33.539.05	21	8 1/2	68	27	2	4
TFG 5	33.539.06	26	10 1/2	78	30	3	4



OSCULATI



Fenders for inflatables

Made of light grey closed cell EVA foam. Preformed, with 350-mm radius for use on inflatables up to 12 metres. Ideal to protect inflatables from impact against wharves and docks.

Code	←→ cm	Thickness cm
33.516.01	25x50	2
33.516.02	33x66	2

